

TECHNICAL INFORMATION

MAX.CARRYING CAPACITANCE OF DRUMS DEPEND ON OUTER DIAMETER OF CABLES

Cable D mm	MD 40	MD 50	MD 60	60	70	80	90	100	120	140	160	180	200
6	420	735	1070	1110	2024	2755							
7	310	540	780	840	1480	2340	2730						
8	235	430	590	640	1064	1463							
9	185	335	465	470	890	1152	2202	2866					
10	150	270	385	388	680	980	1768	2349					
11	14	230	330	315	564	760	1404	1910					
12	100	195	270	254	470	643	1206	1540					
13		165	235	238	385	542	1032	1339	2727				
14		140	210	190	360	454	880	1159	2265	2967			
15		130	185	180	300	430	749	1000	1990	2480			
16		115	160	140	239	358	632	860	1756	2205			
17			145	134	228	294	603	736	1545	1960			
18			130	102	218	280	505	705	1355	1737			
19			120	96	172	228	485	599	1184	1535	2227		
20				92	165	220	402	576	1139	1352	2435	2830	
21				90	159	210	387	485	990	1304	2172	2527	
22				65	122	167	315	468	856	1145	1930	2248	
23				62	117	160	304	389	827	999	1870	2172	2954
24				60	113	156	294	377	709	967	1657	1927	2608
25				58	110	150	285	365	688	839	1608	1867	2522
26				56	80	116	226	299	668	814	1420	1650	2218
27					78	113	220	290	567	700	1244	1450	2150
28					76	109	215	282	550	680	1210	1410	1880
29					73	106	209	226	462	663	1180	1370	1826
30					70	103	162	220	450	564	1028	1200	1583
31						76	157	214	438	550	1003	1166	1540
32						74	153	209	428	537	866	1009	1500
33						72	150	204	352	450	846	985	1289
34							146	158	344	440	828	962	1257
35							108	154	336	430	710	824	1227
36							105	150	329	422	692	806	1040
37							103	148	265	348	678	788	1017
38								144	259	340	664	722	994
39								110	254	334	560	653	972
40								105	249	327	549	640	812
41								102	244	264	539	627	795
42								10	190	259	529	615	779
43									187	254	437	510	763
44									183	249	430	502	750
45									180	254	422	492	610
46									177	240	415	484	600
47									174	187	408	475	589
48									130	184	330	386	578
49									127	180	325	380	568
50									125	178	139	373	558
51									123	175	314	367	442
52									120	172	310	360	435
53										170	305	356	428
54										126	230	280	420
55										124	235	276	414
56										122	232	270	408
57										121	228	267	400
58										119	225	263	304
59										117	222	260	300
60										220	256	295	
61										216	252	290	
62										160	190	287	
63										158	187	282	
64										156	184	280	
65										154	182	275	
66										152	180	270	
67										150	178	266	
68											174	264	